

SAA Sprung lever on a round rose =

features

Supplied with both bolt through and wood screw fixings – AR200FP (701742)

- Nylon understructure – 4 point fixing
- Supplied with HOPPE 105mm full profile spindle (630905)
- Half sets supplied with 8mm x 60mm half spindle – AR229 (630899)
- Sprung Lever suitable for 40mm to 47mm door thickness as standard
- Unsprung Lever suitable for 30mm to 49mm door thickness as standard
- Longer spindles available for thicker doors: See end of this section
- Suitable for 30min and 1 hour fire doors
- Suitable for use with ARNONE Plus escape locks
- LRV Rating: HOPPE F1 Finish LRV of 60, HOPPE F3 Finish LRV of 43.55

standards and certification

Quality & Performance: Successfully type tested to all the requirements of BS EN1906: 2002 Grade 3 (Test reports/certificates are available on request)

*Note: this classification only applies to the product marked with an asterisk

3 7 - 1* 1 4 0 A

Fire Safety: Included on a successful fire test to BS EN1634 Part1: 2002.

Assessed for use on 30 min, & 1 hour fire doors.

Manufactured by an ISO 9000 Registered Company

Conformity Statement: Meets the dimensional recommendations of BS8300 and Approved Document "M"

ID NO PRODUCT REF DESCRIPTION FINISH



Price

£11.50 (Product reference 1918-0)