

TS 55 Circular Plunge Saw

Fast, accurate, safe cutting performance.

1200W soft start motor with full electronic speed control.

Fast-Fix blade changing system

Plunge depth control can be adjusted in one-millimetre steps, from zero to 55mm.

Markers indicate front and rear cutting points of blade at full depth, useful when cutting out apertures with the guide rail.

The cut line stays constant in relation to the base, regardless of blade angle.

Can be used with the Festool Guide Rail System.

Max Depth of Cut @ 45deg: 43mm

Max Depth of Cut @ 90deg: 55mm

Nett Weight: 4.5kg

Power: 1,200W

Rating: Industrial

Speed: 2,000-5,200rpm [Except on 561517]

Spindle Lock: Yes

Blade Dia/Bore: 160mm/20mm

Please note the 561517 is a fixed speed machine.



Price

TS55 with 1.4m Guide Rail, in Systainer, 110v Festool 561311 (Product reference 2577-4161)	£395.00
TS55 without rail, in Systainer, 240v Festool 561429 (Product reference 2577-4163)	£355.00
TS55 without rail, in Systainer, 110v Festool 561431 (Product reference 2577-4164)	£355.00
TS55 with 1.4m Guide Rail, in Systainer, 240v Festool 561515 (Product reference 2577-4165)	£395.00