

Festool Kapex KS 120 EB GB Mitre Saw

The KS 120: a sliding compound mitre saw that combines a high cutting capacity of 120 mm with a compact lightweight design. It achieves the precision needed for high-quality results and provides impressive detail solutions.

- •Twin-column guide for accurate cuts
- •Compact, lightweight design for convenient transportation
- FastFix saw blade changing for adaptation to the working material
- Precision angle transfer via bevel and dual-line laser
- •Fine adjustment of the saw blade angle accurate to the millimetre from the front of the machine
- Safety brake

Main applications

- •Trimming skirting boards and cornices up to 120 mm in height no calculations
- •Cutting boards and panels up to 305 x 88 mm
- •Trimming crown mouldings up to 168 mm in their original wall position
- •Trimming square timber and beams up to 88 mm thick

Supplied with:

- HW universal saw blade W60
- bevel
- workpiece clamp
- operation tool
- in a carton

Versions available:

240v Festool 561285

110v Festool 561286

Technical data:

Power consumption 1600 W

Idle engine speed 1400-3400 min-1

Saw blade diameter 260 mm

Cutting depth 90°/90° 305 x 88 mm

Cutting depth at $45^{\circ}/90^{\circ}$ 215 x 88 mm

Cutting depth 50°/90° (left) 196 x 88 mm

Cutting depth 60°/90° (right) 152 x 88 mm

Cutting depth 45°/45° (left) 215 x 55 mm

Cutting depth 45°/45° (right) 215 x 35 mm

Special cutting depth 90°/90° 60 x 120 mm

Special cut. depth 45°/90° (left) 40 x 120 mm

Special cutting depth 45°/90° 20 x 120 mm

Crown moulding diagonal cut at 90°/90° 168 mm

Crown moulding dia. cut 45°/90° 168 mm

Inclination angle 47/47°

Mitre angle 50/60 °

Bench height (on MFT table available seperately) 923 mm

Dimensions (W x D x H) 713 x 500 x 470 mm



Connection Ø d/e 27/36 mm Weight 21,5 kg



Price

£940.00 (Product reference 3047-0)