

Geo-Fix All Weather

Slate grey 14kg

Product Description

Geo-Fix All Weather Jointing Compound is a unique, ready to use jointing material for all types of paving having joints of 6 mm and over that can be used in both dry and wet conditions. Geo-Fix All Weather Jointing Compound is a quick and easy way of applying a rigid joint on most common paving types including Natural Stone, Concrete, Slate, Clay, Terracotta and Granite.

Benefits

- Supplied ready to use, no mixing required.
- Can be used in both wet and dry conditions.
- Simply brush into joints and compact.
- Cement free – Non staining.
- Sets hard, wont crack or wash out.
- Resists weeds and plant growth.
- Totally weatherproof, unaffected by frost.
- For all joints of 6mm wide and over.
- Water permeable, allows water to escape.

Areas For Use

- Footpaths.
- Outdoor patio areas.
- Indoor stone floor areas.
- Pedestrian areas.
- Driveways subject to light occasional vehicular traffic.

Limitations

- Do not use on joints smaller than 6mm
- Do not apply to dry paving. The paving must be wetted prior to and during application.
- Read all instructions and leaflet carefully before use.
- Joint depth must be a minimum of 25mm
- Do not apply below 30C or if the ground/paving temperature is below 30C.
- In areas subject to vehicular traffic it is essential that the paving elements are bedded on a class 1 mortar and a high percentage of the mortar is squeezed up the joint, thereby providing support for the paving elements.
- GEO-FIX should be considered for its aesthetic and not its structural properties.
- The jointing should not be cleaned by use of high pressure washers until cured for 14 days. The distance between nozzles to jointing must be at least 15cm and a fan nozzle must be used.



Price

£32.51 (Product reference 4302-0)