

# Treatex Hardwax Oil CLEAR GLOSS 1L 2.5L-

## Features

- Easy to apply
- Quick drying
- Low odour
- Should not be used on darker timbers
- Meets with VOC emissions regulations
- Tinted with natural pigments
- Keeps lighter timbers from warming when Hardwax Oil is applied

## Usage

Suitable for: Internal use

Recommended timbers: Lighter coloured timbers e.g. Oak, Pine, Ash, Beech, Birch, Maple, Sycamore etc.

Applications: Floors, doors, stairs, worktops, woodturning etc.

Natural Hardwax Oil contains a small amount of white pigment which allows it to be used in two different ways:

### 1. Base coat:

If you prefer to protect light timbers whilst changing the unfinished colour as little as possible then Treatex Natural Hardwax Oil can be applied as a base coat underneath two coats of Treatex Clear Hardwax Oil to neutralise the warming effect.

### 2. Top coat:

For a purer white, seal Spruce Colour Tone with two coats of Natural Hardwax Oil. When Treatex Clear Hardwax Oil is applied on top of our Spruce Colour Tone it can have a slight yellowing effect on the colour.

## Please Note!

Natural Hardwax Oil is not a complete finish in its own right and should not be used on its own

## Coverage

1L will cover approximately 20m<sup>2</sup> in one coat depending on the timber and method of application.

2.5L will cover approximately 50m<sup>2</sup> in one coat depending on the timber and method of application.



# Price

Treatex Hardwax Oil CLEAR GLOSS 1L + (Product reference 6743-11187)	£23.82
Treatex Hardwax Oil CLEAR GLOSS 2.5L + (Product reference 6743-11188)	£56.82