

## **Treatex Natural Hardwax Oil 11 2.5I-**

**Features** 

- Easy to apply
- Quick drying
- Low odour
- •Should not be used on darker timbers
- •Meets with VOC emissions regulations
- •Tinted with natural pigments
- •Keeps lighter timbers from warming when Hardwax Oil is applied

Usage

Suitable for: Internal use

Recommended timbers: Lighter coloured timbers e.g. Oak, Pine, Ash, Beech, Birch, Maple, Sycamore etc.

Applications: Floors, doors, stairs, worktops, woodturning etc.

Natural Hardwax Oil contains a small amount of white pigment which allows it to be used in two different ways:

1. Base coat:

If you prefer to protect light timbers whilst changing the unfinished colour as little as possible then Treatex Natural Hardwax Oil can be applied as a base coat underneath two coats of Treatex Clear Hardwax Oil to neutralise the warming effect.

2. Top coat:

For a purer white, seal Spruce Colour Tone with two coats of Natural Hardwax Oil. When Treatex Clear Hardwax Oil is applied on top of our Spruce Colour Tone it can have a slight yellowing effect on the colour.

Please Note!

Natural Hardwax Oil is not a complete finish in its own right and should not be used on its own Coverage

1L will cover approximately 20m<sup>2</sup> in one coat depending on the timber and method of application.

2.5L will cover approximately 50m<sup>2</sup> in one coat depending on the timber and method of application.





## **Price**

Treatex Natural Hardwax Oil 1I = (Product reference 6745-11191)	£23.82
Treatex Natural Hardwax Oil 2.5l = (Product reference 6745-11192)	£57.80