

Alpha Chem Acoustic Intumescent Sealant

Cromar Alpha Chem Acoustic Intumescent Sealant is a high quality, one part, flexible 5 hourfire rated sealant used to maintain fire performance in walls, floors and penetration seals. It can also be used to form linear gap seals where gaps are present within the wall and floor construction and linear joints, where wall and floor constructions abutt. The Alpha Chem Sealant also has intumescent properties that cause it to swell upon heating. It also has excellent sound reduction properties and upholds air tightness of buildings.

Ideal for:

- * Sealing and filling openings and joints to maintain fire resistance of walls, floor and structures.
- * Sealing low movement construction joints and service penetrations.
- * Reducing acoustic transfer between building compartments.
- * Maintaining the air tightness of building compartments.
- * Internal use only in gaps up to 50mm, application temperature up to +40°C.

Certifications:

- * Tested in accordance with EN1366-4: 2009 Fire Resistance.
- * Tested in accordance with EN1366-3: 2009 Fire Resistance.
- * Classification to EN13501-2.
- * ULEU & ULUS Listed.
- * Tested in accordance with BS476 pt 20&22 Fire Resistance.
- * Tested in accordance with EN1026 Air Tightness.
- * Tested in accordance with EN10140-2 Sound Reduction.
- * CE Marked.





Price

| AlphaChem Acoustic Intumescent Sealant 295ml Tube (Product reference 8300-19469) | £1.28 |
|---|--------|
| AlphaChem Acoustic Intumescent Sealant 295ml - Box of 12 (Product reference 8300-19470) | £12.75 |
| AlphaChem Acoustic Intumescent Sealant 900ml Tube (Product reference 8300-19471) | £4.65 |
| AlphaChem Acoustic Intumescent Sealant 900ml - Box of 12 (Product reference 8300-19472) | £46.50 |