

# Self-Drilling Tekscrew with 16mm EPDM washer - Coarse Thread

Standard tekscrews for use in fixing cladding and roofing applications.

Features:

- Super hard, super sharp drill tips to ensure fast drill times.
- Hex flange head.
- Screw suitable for 1.2mm - 3.5mm steel.
- Bonded steel washer can act as isolation between substrate and fixture, as an aid to clamping where fixture clearance hole sizes require, and as a weatherseal.
- Coarse thread form (Tek 3)
- EvoShield® coating rated at 500 hours protection against salt spray.



## Price

Tekscrew 5.5 x 26mm - per 250 (Product reference 9557-28442)	£11.44
Tekscrew 5.5 x 32mm - per 250 (Product reference 9557-28443)	£12.60
Tekscrew 5.5 x 38mm - per 250 (Product reference 9557-28444)	£13.37

Tekscrew 5.5 x 50mm - per 100 (Product reference 9557-28445)	£7.06
Tekscrew 5.5 x 60mm - per 100 (Product reference 9557-28446)	£7.72
Tekscrew 5.5 x 75mm - per 100 (Product reference 9557-28447)	£8.84
Tekscrew 5.5 x 100mm - per 100 (Product reference 9557-28448)	£13.90
Tekscrew 5.5 x 125mm - per 100 (Product reference 9557-28449)	£19.54