

# Classic Colour Collection Symphony Blue 520e 1l +

Treatex Classic Colour Collection is a high quality opaque wood finish which has been tried and tested in extreme conditions such as on the coast and in the mountains.

This product is manufactured on a base of natural sustainable raw materials including: sunflower oil, soybean oil, beeswax and carnauba wax.

Treatex Classic Colour Collection can be used on all types of timber and is the ideal finish for doors, windows, fences, sheds, cladding, kitchen cabinets and other interior or exterior joinery.

## technical specifications

Brand Treatex

Colour Range Classic Colour Collection

Coverage 1L covers approximately 25m<sup>2</sup> in one coat depending on the timber and method of application.

MPN 520E

GTIN 5060310661181

## overview

- Easy to apply
- High coverage
- UV resistant
- Will not flake or peel
- Contains no biocides or preservatives
- Highly water resistant
- For interior or exterior use
- All timber types

- Doors, windows, fences, sheds, cladding and kitchen cabinets

## preparation

Treatex Classic Colour Collection works best on unfinished timber.

Previous porous finishes should be thoroughly cleaned or lightly sanded before overcoating.

Flaking or peeling finishes must be fully removed prior to application.

A trial application is essential when overcoating another finish.

Ensure the timber is dry and free from possible contaminants e.g. algae, grease, dirt, dust etc.

Exterior timbers susceptible to decay, mould and fungi should be treated first with a preservative.

To help prevent staining, exterior timbers with high tannin levels (e.g. oak, idigbo, teak, cedar, mahogany) should be treated with Treatex Stain Inhibitor.

We advise that when using Treatex Classic Colour Collection, sufficient product is purchased to complete the whole project and when more than one tin is required it is advisable to mix them together before use.

Timber must have a moisture content below 18%.

Temperature must be greater than 8°

## Application

Stir tins thoroughly, before and during use.

Use a brush or roller to evenly apply

Treatex Classic Colour Collection in the same direction as the wood grain, allowing approximately 40ml per m<sup>2</sup>.

If possible, apply the first coat to all sides of the wood before installation.

Pay particular attention to any end grain.

To ensure the timber is fully sealed apply the product liberally on end grain.

After approximately 12 hours drying the first coat can be overcoated.

Apply with a brush or roller a second coat of Treatex Classic Colour Collection, again allowing roughly 40ml per m<sup>2</sup>.

After the second coat, leave for approximately 12-24 hours to dry.

A third coat may be needed if applying a light colour on a dark timber.

One coat may be enough when renovating previously porous finishes.

#### aftercare

Store tins in a cool and frost free environment.

Unopened tins will last for five years.

Once tins are opened, transfer contents to smaller airtight container.

For a different sheen level on internal timbers Treatex Classic Colour Collection can be overcoated with Treatex Hardwax Oil Clear Matt, Satin or Gloss.



## Price

£23.71 (Product reference 7422-0)