

502 Wood Adhesive

Also check - Internal D3 Adhesive on our web site.

EVERBUILD ALL PURPOSE WATERPROOF WOOD ADHESIVE is a medium viscosity, resin based polymer emulsion which exceeds the water resistance requirements of BS EN204 D3. The product is also suitable for load bearing work as it conforms fully to the BS 14256 Sustained Load requirements.

Benefits

Excellent rate of bond strength development.

High degree of water resistance. D3 Classification- joints may be subject to short term water contact or exposure to high humidity. Interior/exterior use.

Low timber staining characteristics - will not stain.

Creep Resistant.

Dries clear - contains no inert fillers.

Water based - environmentally friendly/easy clean up.

Suitable for radio frequency cure.

Areas For Use

As a waterproof/creep resistant wood adhesive, internally and externally.

Limitations

Not suitable for continuous immersion.

Ensure wood doesn't contain excessive moisture (<15%)

Do not use at temperatures below 10oC.

Note: drying time is extended at low temperatures.

Clean excess adhesive off glue line after clamping before adhesive dries with a damp cloth..

Sand off any excess adhesive before staining the wood.

Ensure sufficient clamping pressure, especially important with radio frequency bonding.

Use on Laminates: Only suitable for bonding small porous laminate strips. Do not use on non-porous or large areas of laminate. Use CONTACT ADHESIVE.





Price

502 Wood Adhesive - Box 12 - 1 Litre bottles (Product reference 775-379)	£52.80
502 Wood Adhesive Per IL Bottle (Product reference 775-380)	£4.40
502 Wood Adhesive Per 5L Bottle (Product reference 775-381)	£15.80